

Solis



FRONT LOADER



SALIENT FEATURES

- Simple & Easy to use Level Indicator.
- Automatic Self Level at time of loading
- Vesconite bushes in all wear points for easy maintenance.
- Quick change attachments & lever system for Easy operation.
- Greasable plated pins for Easy maintenance.
- Easy to store with stand.

FRONT END LOADER SPECIFICATIONS

| Model No. | 2400 | 3200 | 3500 | 5500 | 7300 | 8300 | 8700 | 9500 |
|---|--------|-------|----------|----------|--------|---------|--------|--------|
| H.P. | 20 | 26 | 35 | 45 & 50 | 60 | 75 & 90 | 100 | 110 |
| Bucket Width (m) | 1.2 | 1.2 | 1.35/1.5 | 1.5/1.65 | 1.8 | 1.8 | 2.1 | 2.1 |
| S.W.L. (Std Bucket) | 280 kg | 300kg | 550kg | 800kg | 1000kg | 1000kg | 1200kg | 1500kg |
| Pin Height (mm) | 1800 | 1900 | 2400 | 2700 | 3100 | 3500 | 3720 | 4050 |
| Dump Height (mm) | 1400 | 1450 | 1860 | 1990 | 2300 | 2700 | 2920 | 3900 |
| Dig Depth (mm) | 60 | 60 | 80 | 100 | 150 | 150 | 151 | 152 |
| Crowd Angle | 25° | 25° | 25° | 35° | 40° | 40° | 40° | 40° |
| Dump Angle | 40° | 40° | 40° | 65° | 50° | 50° | 60° | 60° |
| Front End Loader Weight (including Subframe) | 170kg | 250kg | 350kg | 550kg | 800kg | 800kg | 950kg | 950kg |



SOLIS



INTERNATIONAL TRACTORS LIMITED

H.O: Plot no. 29 & 31, Aggarwal Mall, CBD Ground, Near Karkardooma Court, Delhi - 110032 (INDIA). | Phone: +91 11 22600700, Fax: +91 11 22377472
 Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221 | Fax: +91 1882 302293
 Email: exports@sonalika.com | Url: www.sonalika.com

Follow us on: [f](https://www.facebook.com/SonalikaTractors) www.facebook.com/SonalikaTractors; [t](https://www.twitter.com/SonalikaTractors) www.twitter.com/SonalikaTractors; [in](https://www.linkedin.com/groups/Sonalika-Tractors) www.linkedin.com/groups/Sonalika-Tractors